

SGP(配管用炭素鋼鋼管)				STPG(圧力配管用炭素鋼鋼管)						
口径	外径	厚さ	重量(M)	スケジュール40			スケジュール80		スケジュール160	
				外径	厚さ	重量(M)	厚さ	重量(M)	厚さ	重量(M)
6A	10.5			10.5	1.7	0.369	2.4	0.479		
8A	13.8			13.8	2.2	0.629	3.0	0.799		
10A	17.3			17.3	2.3	0.851	3.2	1.11		
15A	21.7	2.8	1.3	21.7	2.8	1.31	3.7	1.64	4.7	1.97
20A	27.2	2.8	1.7	27.2	2.9	1.74	3.9	2.24	5.5	2.94
25A	34.0	3.2	2.4	34.0	3.4	2.57	4.5	3.27	6.4	4.36
32A	42.7	3.5	3.4	42.7	3.6	3.47	4.9	4.57	6.4	5.73
40A	48.6	3.5	3.9	48.6	3.7	4.10	5.1	5.47	7.1	7.27
50A	60.5	3.8	5.3	60.5	3.9	5.44	5.5	7.46	8.7	11.1
65A	76.3	4.2	7.5	76.3	5.2	9.12	7.0	12.0	9.5	15.6
80A	89.1	4.2	8.8	89.1	5.5	11.30	7.6	15.3	11.1	21.4
100A	114.3	4.5	12.2	114.3	6.0	16.0	8.6	22.4	13.5	33.6
125A	139.8	4.5	15.0	139.8	6.6	21.7	9.5	30.5	15.9	48.6
150A	165.2	5.0	19.8	165.2	7.1	27.7	11.0	41.8	18.2	66.0
200A	216.3	5.8	30.1	216.3	8.2	42.1	12.7	63.8	23.0	110
250A	267.4	6.6	42.4	267.4	9.3	59.2	15.1	93.9	28.6	168
300A	318.5	6.9	53.0	318.5	10.3	78.3	17.4	129	33.3	234
350A	355.6	7.9	67.7	355.6	11.1	94.3	19.0	158	35.7	282
400A	406.4	7.9	77.6	406.4	12.7	123	21.4	203	40.5	365
450A	457.2	7.9	87.5	457.2	14.3	156	23.8	254	45.2	459
500A	508.0	7.9	97.4	508.0	15.1	184	26.2	311	50.0	565

配管用ステンレス鋼鋼管(重量はSUS304の値)												
口径	外径	厚さ	重量(M)	スケジュール5		スケジュール10		スケジュール20		2mm	3mm	4mm
				厚さ	重量(M)	厚さ	重量(M)	厚さ	重量(M)	重量(M)	重量(M)	重量(M)
6A	10.5	1.0	0.237	1.2	0.278	1.5	0.336	0.423				
8A	13.8	1.2	0.377	1.65	0.499	2.0	0.588	0.588	0.807			
10A	17.3	1.2	0.481	1.65	0.643	2.0	0.762	0.762	1.07			
15A	21.7	1.7	0.824	2.1	1.03	2.5	1.20	0.981	1.40			
20A	27.2	1.7	1.05	2.1	1.31	2.5	1.54	1.26	1.81			
25A	34.0	1.7	1.33	2.8	2.18	3.0	2.32	1.59	2.32	2.99		
32A	42.7	1.7	1.69	2.8	2.78	3.0	2.97	2.03	2.97	3.86		
40A	48.6	1.7	1.93	2.8	3.19	3.0	3.41	2.32	3.41	4.44		
50A	60.5	1.7	2.42	2.8	4.02	3.5	4.97	2.91	4.30	5.63		
65A	76.3	2.1	3.88	3.0	5.48	3.5	6.35	3.70	5.48	7.20		
80A	89.1	2.1	4.55	3.0	6.43	4.0	8.48	4.34	6.43	8.48		
100A	114.3	2.1	5.87	3.0	8.32	4.0	11.0	5.59	8.32	11.0		
125A	139.8	2.8	9.56	3.4	11.6	5.0	16.8		10.2	13.5		
150A	165.2	2.8	11.3	3.4	13.7	5.0	20.0		12.1	16.1		
200A	216.3	2.8	14.9	4.0	21.2	6.5	34.0		15.9	21.2		
250A	267.4	3.4	22.4	4.0	26.2	6.5	42.2		19.8	26.2		
300A	318.5	4.0	31.3	4.5	35.2	6.5	50.5		23.6	31.3		

一般配管用ステンレス鋼管(SUS304)			
口径	外径	厚さ	重量(M)
13su	15.88	0.8	0.301
20su	22.22	1.0	0.529
25su	28.58	1.0	0.687
30su	34.0	1.2	0.980
40su	42.7	1.2	1.24
50su	48.6	1.2	1.42
60su	60.5	1.5	2.20
75su	76.3	1.5	2.79
80su	89.1	2.0	4.34
100su	114.3	2.0	5.59
125su	139.8	2.0	6.87
150su	165.2	3.0	12.1
200su	216.3	3.0	15.9
250su	267.4	3.0	19.8
300su	318.5	3.0	23.6

塩ビパイプ										
口径	VP,HIVP,HTVP			VP	HIVP	HTVP	VU			
	外径	内径	厚さ				重量(M)	外径	内径	厚さ
13A	18	13	2.5	0.174	0.170	0.180				
16A	22	16	3.0	0.256	0.251	0.265				
20A	26	20	3.0	0.310	0.303	0.321				
25A	32	25	3.5	0.448	0.439	0.464				
30A	38	31	3.5	0.542	0.531	0.561				
40A	48	40	4.0	0.791	0.774	0.818	48	44	2.0	0.413
50A	60	51	4.5	1.122	1.098	1.161	60	56	2.0	0.521
65A	76	67	4.5	1.445	1.415	1.506	76	71	2.5	0.825
80A	89	77	5.9	2.202	2.156	2.294	89	83	3.0	1.159
100A	114	100	7.1	3.409	3.338	3.552	114	107	3.5	1.737
125A	140	125	7.5	4.464	4.370	4.651	140	131	4.5	2.739
150A	165	146	9.6	6.701	6.561	6.982	165	154	5.5	3.941
200A	216	194	11.0	10.129	9.918	10.554	216	202	7.0	6.572
250A	267	240	13.6				267	250	8.4	9.758
300A	318	286	16.2				318	298	9.9	13.701
350A							370	348	11.2	18.051
400A							420	395	12.6	23.059
450A							470	442	14.1	28.875
500A							520	489	15.6	35.346
600A							630	592	19.2	